

On/Off, Spring return, 24 V



5-year warranty



Technical data

Electrical data		
Nominal voltage	AC/DC 24 V	
Nominal voltage frequency	50/60 Hz	
Nominal voltage range	AC 19.2...28.8 V / DC 21.6...28.8 V	
Power consumption in operation	5 W	
Power consumption in rest position	2.5 W	
Transformer sizing	7.5 VA	
Electrical Connection	18 GA appliance cable, 3 ft [1 m], with 1/2" NPT conduit connector	
Overload Protection	electronic throughout 0...95° rotation	
Functional data		
Position feedback U note	No Feedback	
Direction of motion motor	selectable by ccw/cw mounting	
Direction of motion fail-safe	reversible with cw/ccw mounting	
Manual override	5 mm hex crank (3/16" Allen), supplied	
Angle of rotation	95°	
Running Time (Motor)	75 s / 90°	
Running time fail-safe	<20 s	
Noise level, motor	50 dB(A)	
Noise level, fail-safe	62 dB(A)	
Position indication	Mechanical	
Safety data		
Power source UL	Class 2 Supply	
Degree of protection IEC/EN	IP54	
Degree of protection NEMA/UL	NEMA 2	
Enclosure	UL Enclosure Type 2	
Agency Listing	cULus acc. to UL60730-1A/-2-14, CAN/CSA E60730-1:02, CE acc. to 2014/30/EU	
Quality Standard	ISO 9001	
UL 2043 Compliant	Suitable for use in air plenums per Section 300.22(C) of the NEC and Section 602 of the IMC	
Ambient humidity	Max. 95% RH, non-condensing	
Ambient temperature	-22...122°F [-30...50°C]	
Storage temperature	-40...176°F [-40...80°C]	
Servicing	maintenance-free	
Weight		
Weight	4.5 lb [2.0 kg]	
Materials		
Housing material	Galvanized steel and plastic housing	

Technical data

Footnotes †Rated Impulse Voltage 4kV, Type of action 1.AA, Control Pollution Degree 3.

Electrical installation

**Warning! Live electrical components!**

During installation, testing, servicing and troubleshooting of this product, it may be necessary to work with live electrical components. Have a qualified licensed electrician or other individual who has been properly trained in handling live electrical components perform these tasks. Failure to follow all electrical safety precautions when exposed to live electrical components could result in death or serious injury.



(A) Actuators with appliance cables are numbered.



(1) Provide overload protection and disconnect as required.



(3) Actuators may also be powered by DC 24 V.



(45) Actuators may be powered in parallel. Power consumption must be observed.



(48) Parallel wiring required for piggy-back applications.



◆ Meets cULus requirements without the need of an electrical ground connection.

Wiring diagrams

On/Off

