

# TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Catalog Page

## Description

The TEC3000 Color Series Thermostat Controllers are wireless, stand-alone, and field-selectable BACnet® MS/TP or N2 networked devices that provide on/off, floating, and proportional control of the following:

- Local hydronic reheat valves
- Pressure-dependent VAV equipment with or without local reheat
- Two- or four-pipe fan coils
- Cabinet unit heaters
- Other zoning equipment using an on/off, floating, or 0 to 10 VDC proportional control input
- Single- or two-stage control of unitary rooftop units (RTUs)
- Single- or two-stage control of RTUs with economizers
- Single- or two-stage control of heat pumps
- Single- or two-stage control of heat pumps with economizers

You can remote monitor and program the wireless and field-selectable BACnet MS/TP or N2 networked thermostat controllers through the building automation system, for efficient space temperature control. The wireless thermostat controllers feature a connection to the ZFR Pro wireless network. All models include a USB port configuration that reduces installation time by allowing simple backup and restore features from a USB drive, which enables rapid cloning of configuration between like units. The programming memory of all TEC3000 Series Thermostat Controllers is non-volatile.

Some models feature a built-in occupancy sensing capability. These thermostat controllers use additional standby setpoints to maximize up to 30% energy savings in high-energy usage commercial buildings, such as schools and hotels, during occupied times.

A bright, high-definition capacitive touchscreen display provides responsive feedback and improved readability of text and icons. The home screen is configurable to Modern and Classic, and Light and Dark themes.

Models are available in modern black or white high-gloss designs with or without the Johnson Controls® logo.

The following fan configurations are supported for fan coil equipment types:

- Single-speed
- Multi-speed (two or three discrete speeds)
- Variable-speed/EC motors (0 to 10 VDC control)

All models support dehumidification on two-pipe fan coil units with reheat, and four-pipe fan coil units with or without reheat.

When no heating is required and mechanical cooling is available, the thermostat controller monitors space humidity and activates dehumidification control as necessary. Heat or reheat is used as required to maintain the space temperature.

For optimal dehumidification performance, use a fan coil unit that includes a multi-speed or variable-speed fan (VSF).

Refer to the *TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Product Bulletin (LIT-12013193)* for important product application information.

## Features and benefits

- **Two configurable binary inputs**—Provide additional inputs for advanced functions such as remote night setback, service or filter alarms, motion detector, and window status.
- **Field-Selectable BACnet MS/TP or N2 Networked Communication (TEC36xx-1x-000 Models)**—Simplifies the upgrade from N2 networked communication to BACnet MS/TP networked communication without changing hardware.
- **USB port configuration**—Rapidly clone the configuration between like units through simple backup and restore features from a USB drive to reduce installation time.
- **Programmable in seven languages**—Provides English, Spanish, French, German, Italian, Dutch, Portuguese (requires a downloadable language pack).
- **Backlit full-color liquid crystal display (LCD)**—Offers an intuitive color backlit display that makes setup and operation quick and easy. The new display features on all models and offers real-time control status of the environment in easy-to-read, plain text messages with an adjustable backlight that brightens during user interaction.
- **Configurable touchscreen UI**—Facility managers can limit the user interaction with the thermostat controller display based on specific energy policies.
- **Various models available**—Offers models in modern black<sup>1</sup> or white<sup>2</sup> high-gloss designs with or without the Johnson Controls logo.
- 1. The color code of the black used for the TEC3000 Color Series is: hex #2d2926 or RAL 9017.
- 2. The color code of the white used for the TEC3000 Color Series is: hex #F4F5F0 or RAL 9016

**TEC3000 Color Series Thermostat Controller shown with and without occupancy sensor in white and black enclosures**



- **End-of-line switch**—Simplifies the layout and installation of communication buses.
- **Mobile Access Portal (MAP) Gateway compatibility (MAP Release 4.0 or later)**—View the equipment and control the conditions through your mobile devices.
- **Onboard occupancy sensor (TEC3031-1x-000 and TEC3xx3-1x-000 Models)**—Provides energy savings in high-energy usage commercial buildings without additional installation time or cost.
- **Integral humidity sensor**—Monitors space humidity on all models. Activates dehumidification control on two-pipe fan coil units with reheat and four-pipe fan coil units with or without reheat.
- **Multiple fan configurations for fan coil equipment types**—Provide field-selectable single-speed, multi-speed, and variable-speed fan control capabilities.
- **Full line of remote TE-6300 Series Temperature Sensors**—Support a wide usage commercial buildings without additional installation time or cost.
- **Built-in schedule object**—Allows all wireless and wired models of thermostat controllers to be scheduled as stand-alone devices; allows wireless and BACnet MS/TP models to be defined and adjusted through the building automation system.
- **Optimal start**—Allows each thermostat controller to anticipate the heating or cooling needs of a space by starting the equipment early enough to reach the setpoint at the beginning of the scheduled occupancy.

## **TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Catalog Page (Continued)**

- **Auto-tuned control loops**—Reduce commissioning time, eliminate change-of-season recommissioning, and reduce wear and tear of the mechanical devices.
- **Load shed**—Commands a load shed input to offset the heating and cooling setpoints by a fixed amount on networked models. The change rate of the setpoints is

adjustable. The load shed feature is in place to help satisfy the California Title 24 requirements that are defined in joint appendix JA5, section JA5.2.4 for demand signal response. The trigger for this event is defined in another controller and passed through the network command.

### **Repair information**

If the TEC3000 Color Series Thermostat Controllers fails to operate within its specifications, replace the unit. For a replacement TEC3000 Thermostat Controller contact the nearest Johnson Controls® representative.

### **Selection charts**

Wireless thermostat controller models

| Code number    | Control output                                     | Occupancy | Dehumidification | Johnson Controls logo | Color |
|----------------|--|-----------|------------------|-----------------------|-------|
| TEC3012-13-000 | On/off or floating fan coil and zoning             | No        | Yes              | Yes                   | Black |
| TEC3012-14-000 | On/off or floating fan coil and zoning             | No        | Yes              | Yes                   | White |
| TEC3012-15-000 | On/off or floating fan coil and zoning             | No        | Yes              | No                    | Black |
| TEC3012-16-000 | On/off or floating fan coil and zoning             | No        | Yes              | No                    | White |
| TEC3013-13-000 | On/off or floating fan coil and zoning             | Yes       | Yes              | Yes                   | Black |
| TEC3013-14-000 | On/off or floating fan coil and zoning             | Yes       | Yes              | Yes                   | White |
| TEC3013-15-000 | On/off or floating fan coil and zoning             | Yes       | Yes              | No                    | Black |
| TEC3013-16-000 | On/off or floating fan coil and zoning             | Yes       | Yes              | No                    | White |
| TEC3022-13-000 | 0 to 10 VDC proportional fan coil and zoning       | No        | Yes              | Yes                   | Black |
| TEC3022-14-000 | 0 to 10 VDC proportional fan coil and zoning       | No        | Yes              | Yes                   | White |
| TEC3022-15-000 | 0 to 10 VDC proportional fan coil and zoning       | No        | Yes              | No                    | Black |
| TEC3022-16-000 | 0 to 10 VDC proportional fan coil and zoning       | No        | Yes              | No                    | White |
| TEC3023-13-000 | 0 to 10 VDC proportional fan coil and zoning       | Yes       | Yes              | Yes                   | Black |
| TEC3023-14-000 | 0 to 10 VDC proportional fan coil and zoning       | Yes       | Yes              | Yes                   | White |
| TEC3023-15-000 | 0 to 10 VDC proportional fan coil and zoning       | Yes       | Yes              | No                    | Black |
| TEC3023-16-000 | 0 to 10 VDC proportional fan coil and zoning       | Yes       | Yes              | No                    | White |
| TEC3030-13-000 | Single- or two-stage RTU/heat pump with economizer | No        | No               | Yes                   | Black |
| TEC3030-14-000 | Single- or two-stage RTU/heat pump with economizer | No        | No               | Yes                   | White |
| TEC3030-15-000 | Single- or two-stage RTU/heat pump with economizer | No        | No               | No                    | Black |
| TEC3030-16-000 | Single- or two-stage RTU/heat pump with economizer | No        | No               | No                    | White |

**TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Catalog Page (Continued)**

Wireless thermostat controller models (Continued)

| Code number    | Control output                                     | Occupancy | Dehumidification | Johnson Controls logo | Color |
|----------------|--|-----------|------------------|-----------------------|-------|
| TEC3031-13-000 | Single- or two-stage RTU/heat pump with economizer | Yes       | No               | Yes                   | Black |
| TEC3031-14-000 | Single- or two-stage RTU/heat pump with economizer | Yes       | No               | Yes                   | White |
| TEC3031-15-000 | Single- or two-stage RTU/heat pump with economizer | Yes       | No               | No                    | Black |
| TEC3031-16-000 | Single- or two-stage RTU/heat pump with economizer | Yes       | No               | No                    | White |

Stand-alone thermostat controller models

| Code number    | Control output                                     | Occupancy | Dehumidification | Johnson Controls logo | Color |
|----------------|--|-----------|------------------|-----------------------|-------|
| TEC3312-13-000 | On/off or floating fan coil and zoning             | No        | Yes              | Yes                   | Black |
| TEC3312-14-000 | On/off or floating fan coil and zoning             | No        | Yes              | Yes                   | White |
| TEC3312-15-000 | On/off or floating fan coil and zoning             | No        | Yes              | No                    | Black |
| TEC3312-16-000 | On/off or floating fan coil and zoning             | No        | Yes              | No                    | White |
| TEC3313-13-000 | On/off or floating fan coil and zoning             | Yes       | Yes              | Yes                   | Black |
| TEC3313-14-000 | On/off or floating fan coil and zoning             | Yes       | Yes              | Yes                   | White |
| TEC3313-15-000 | On/off or floating fan coil and zoning             | Yes       | Yes              | No                    | Black |
| TEC3313-16-000 | On/off or floating fan coil and zoning             | Yes       | Yes              | No                    | White |
| TEC3322-13-000 | 0 to 10 VDC proportional fan coil and zoning       | No        | Yes              | Yes                   | Black |
| TEC3322-14-000 | 0 to 10 VDC proportional fan coil and zoning       | No        | Yes              | Yes                   | White |
| TEC3322-15-000 | 0 to 10 VDC proportional fan coil and zoning       | No        | Yes              | No                    | Black |
| TEC3322-16-000 | 0 to 10 VDC proportional fan coil and zoning       | No        | Yes              | No                    | White |
| TEC3323-13-000 | 0 to 10 VDC proportional fan coil and zoning       | Yes       | Yes              | Yes                   | Black |
| TEC3323-14-000 | 0 to 10 VDC proportional fan coil and zoning       | Yes       | Yes              | Yes                   | White |
| TEC3323-15-000 | 0 to 10 VDC proportional fan coil and zoning       | Yes       | Yes              | No                    | Black |
| TEC3323-16-000 | 0 to 10 VDC proportional fan coil and zoning       | Yes       | Yes              | No                    | White |
| TEC3330-13-000 | Single- or two-stage RTU/heat pump with economizer | No        | No               | Yes                   | Black |
| TEC3330-14-000 | Single- or two-stage RTU/heat pump with economizer | No        | No               | Yes                   | White |

**TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Catalog Page (Continued)**

Stand-alone thermostat controller models (Continued)

| Code number    | Control output   | Occupancy | Dehumidification | Johnson Controls logo | Color |
|----------------|--|-----------|------------------|-----------------------|-------|
| TEC3330-15-000 | Single- or two-stage RTU/<br>heat pump with economizer | No        | No               | No                    | Black |
| TEC3330-16-000 | Single- or two-stage RTU/<br>heat pump with economizer | No        | No               | No                    | White |
| TEC3331-13-000 | Single- or two-stage RTU/<br>heat pump with economizer | Yes       | No               | Yes                   | Black |
| TEC3331-14-000 | Single- or two-stage RTU/<br>heat pump with economizer | Yes       | No               | Yes                   | White |
| TEC3331-15-000 | Single- or two-stage RTU/<br>heat pump with economizer | Yes       | No               | No                    | Black |
| TEC3331-16-000 | Single- or two-stage RTU/<br>heat pump with economizer | Yes       | No               | No                    | White |

Field-selectable BACnet MS/TP or N2 Networked Thermostat Controller models

| Code number    | Control output                               | Occupancy | Dehumidification | Johnson Controls logo | Color |
|----------------|--|-----------|------------------|-----------------------|-------|
| TEC3612-13-000 | On/off or floating fan coil and zoning       | No        | Yes              | Yes                   | Black |
| TEC3612-14-000 | On/off or floating fan coil and zoning       | No        | Yes              | Yes                   | White |
| TEC3612-15-000 | On/off or floating fan coil and zoning       | No        | Yes              | No                    | Black |
| TEC3612-16-000 | On/off or floating fan coil and zoning       | No        | Yes              | No                    | White |
| TEC3613-13-000 | On/off or floating fan coil and zoning       | Yes       | Yes              | Yes                   | Black |
| TEC3613-14-000 | On/off or floating fan coil and zoning       | Yes       | Yes              | Yes                   | White |
| TEC3613-15-000 | On/off or floating fan coil and zoning       | Yes       | Yes              | No                    | Black |
| TEC3613-16-000 | On/off or floating fan coil and zoning       | Yes       | Yes              | No                    | White |
| TEC3622-13-000 | 0 to 10 VDC proportional fan coil and zoning | No        | Yes              | Yes                   | Black |
| TEC3622-14-000 | 0 to 10 VDC proportional fan coil and zoning | No        | Yes              | Yes                   | White |
| TEC3622-15-000 | 0 to 10 VDC proportional fan coil and zoning | No        | Yes              | No                    | Black |
| TEC3622-16-000 | 0 to 10 VDC proportional fan coil and zoning | No        | Yes              | No                    | White |
| TEC3623-13-000 | 0 to 10 VDC proportional fan coil and zoning | Yes       | Yes              | Yes                   | Black |
| TEC3623-14-000 | 0 to 10 VDC proportional fan coil and zoning | Yes       | Yes              | Yes                   | White |
| TEC3623-15-000 | 0 to 10 VDC proportional fan coil and zoning | Yes       | Yes              | No                    | Black |
| TEC3623-16-000 | 0 to 10 VDC proportional fan coil and zoning | Yes       | Yes              | No                    | White |

The performance specifications are nominal and conform to acceptable industry standards. For applications at conditions beyond these specifications, consult the local Johnson Controls office. Johnson Controls shall not be liable for damages resulting from misapplication or misuse of its products. © 2019 Johnson Controls.

[www.johnsoncontrols.com](http://www.johnsoncontrols.com)

## **TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Catalog Page (Continued)**

Field-selectable BACnet MS/TP or N2 Networked Thermostat Controller models (Continued)

| Code number    | Control output   | Occupancy | Dehumidification | Johnson Controls logo | Color |
|----------------|--|-----------|------------------|-----------------------|-------|
| TEC3630-13-000 | Single- or two-stage RTU/<br>heat pump with economizer | No        | No               | Yes                   | Black |
| TEC3630-14-000 | Single- or two-stage RTU/<br>heat pump with economizer | No        | No               | Yes                   | White |
| TEC3630-15-000 | Single- or two-stage RTU/<br>heat pump with economizer | No        | No               | No                    | Black |
| TEC3630-16-000 | Single- or two-stage RTU/<br>heat pump with economizer | No        | No               | No                    | White |
| TEC3631-13-000 | Single- or two-stage RTU/<br>heat pump with economizer | Yes       | No               | Yes                   | Black |
| TEC3631-14-000 | Single- or two-stage RTU/<br>heat pump with economizer | Yes       | No               | Yes                   | White |
| TEC3631-15-000 | Single- or two-stage RTU/<br>heat pump with economizer | Yes       | No               | No                    | Black |
| TEC3631-16-000 | Single- or two-stage RTU/<br>heat pump with economizer | Yes       | No               | No                    | White |

### **Accessories**

| Code number                 | Description  |
|-----------------------------|--|
| TEC-WALLPLT                 | Wallplate for retrofitting existing installations or concealing mounting surface damage; can be used with any TEC3000 Color Series Thermostat Controller |
| MS-WNC1820-0A               | WNC1800-0SZ with base, 120 to 230 VAC power, ZFR1820 ProCordFlag, with 3 ft (0.9 m) cable  |
| MS-WNC1823-0A               | WNC1800-0SZ with base, 120 to 230 VAC power, ZFR1823 ProCordWall, with 10 ft (3 m) cable   |
| MS-WNC1820-0B               | WNC1800-0SZ with base, 24 VAC power, ZFR1820 ProCordFlag, with 3 ft (0.9 m) cable  |
| MS-WNC1823-0B               | WNC1800-0SZ with base, 24 VAC power, ZFR1823 ProCordWall, with 10 ft (3 m) cable   |
| MS-ZFR1821-0B               | ZFR1821 Pro Flag Repeater, 24 VAC/DC power, with 3 ft (0.9 m) cable  |
| MS-ZFR1822-0B               | ZFR1822 Pro Wall Mount Repeater, 24 VAC/DC power, with 10 ft (3 m) cable   |
| MS-ZFR1821-0                | ZFR1821 Pro Flag Router, with 3 ft (0.9 m) cable   |
| MS-ZFR1822-0                | ZFR1822 Pro Wall Mount Router, with 10 ft (3 m) cable  |
| ZFR-CBLEXT-0                | 10 ft (3 m) extension cable accessory, RJ12 F-F coupler  |
| ZFR-WALLCOVER               | ZFR Repeater wallplate cover   |
| ZFR-USBHA-0                 | Wireless USB dongle  |
| TE-6300 Series <sup>1</sup> | Remote temperature sensors   |
| T-4000-119                  | Allen-head adjustment tool (30 per bag)  |

1. Refer to the *TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Product Bulletin (LIT-12013193)* for ordering details regarding Johnson Controls TE-6300 Series Remote Temperature Sensors.

## **TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Catalog Page (Continued)**

### **Technical specifications**

#### **TEC3000 Color Series Thermostat Controllers**

|   |  |   |
|---|--|---|
| <b>Power requirements</b>   |  | 19 to 30 VAC, 50/60 Hz, 4 VA at 24 VAC nominal, Class 2 or safety extra-low voltage (SELV)      |
| <b>USB port power rating</b>  |  | 120 to 250 mA current draw supported  |
| <b>Analog output rating (for TEC3x2x models)</b>                      |  | 0 to 10 VDC into 2k ohm resistance (minimum)  |
| Relay contact rating (for TEC3x1x and TEC3x3x models)                 | On/off or floating control (for TEC3x1x models)  | 19 to 30 VAC, 1.0 A maximum, 15 mA minimum, 3.0 A in-rush, Class 2 or SELV                      |
| Fan relay output rating (for TEC3x1x and TEC3x2x models)              |  | 19 to 30 VAC, 1.0 A maximum, 15 mA minimum, 3.0 A in-rush                                       |
| Auxiliary output rating/triac output (for TEC3x1x and TEC3x2x models) |  | 19 to 30 VAC, 1.0 A maximum, 15 mA minimum, 3.0 A in-rush                                       |
| <b>Binary inputs</b>  | <b>For TEC3x1x and TEC3x2x models:</b> Dry contact across terminal COM to terminals BI1, BI2, or COS   |   |
|   | <b>For TEC3x3x models:</b> Dry contact across terminal COM to terminals BI1 or BI2   |   |
| <b>Analog inputs</b>  | <b>For TEC3x1x and TEC3x2x models (two Al)s:</b> Nickel, platinum, A99B, 2.25k ohm NTC, 10k ohm NTC, 10k ohm NTC Type 3 across terminal COM to terminals R SEN or COS, 0-10 VDC  |   |
|   | <b>For TEC3x3x models (three Al)s:</b> Nickel, platinum, A99B, 2.25k ohm NTC, 10k ohm NTC, 10k ohm NTC Type 3 across terminal COM to terminals R SEN, SAT, or OAT, 0-10 VDC  |   |
| <b>Temperature and humidity sensor type</b>                           | Local digital sensor   |   |
| <b>Wire size</b>  | 18 AWG (1.0 mm diameter) maximum, 22 AWG (0.6 mm diameter) recommended   |   |
| <b>MS/TP network guidelines</b>                                       | <b>For wired models:</b> Up to 100 devices maximum for each Network Automation Engine (NAE); 4,000 ft (1,219 m) maximum cable length. Refer to the MS/TP Technical Bulletin for the Metasys, FX, or Verasys® system installed. |   |
|   | <b>For wireless models:</b> Up to 100 devices maximum for each Network Automation Engine (NAE)   |   |
| <b>Wireless band (for wireless models)</b>                            | Direct-sequence spread-spectrum 2.4 GHz ISM bands  |   |
| <b>Transmission power (for wireless models)</b>                       | 10 mW maximum  |   |
| <b>Transmission range (for wireless models)</b>                       | 50 ft (15.2 m) recommended indoor  |   |
|   | 250 ft (76.2 m) line of sight, maximum   |   |
| <b>Temperature range</b>  | <b>Backlit display</b>   | -40.0°F/-40.0°C to 122.0°F/50.0°C in 0.5° increments  |
|   | <b>Heating control</b>   | 40.0°F/4.5°C to 90.0°F/32.0°C   |
|   | <b>Cooling control</b>   | 54.0°F/12.0°C to 100.0°F/38.0°C   |
| <b>Accuracy</b>   | <b>Temperature</b>   | ±0.9°F/±0.5°C at 70.0°F/21.0°C typical calibrated   |
|   | <b>Humidity</b>  | ±5% RH from 20% to 80% RH at 50°F to 90°F (10°C to 32°C)  |
| <b>Minimum deadband</b>   |  | 2°F/1°C between heating and cooling   |
| <b>Occupancy sensor motion detection (occupancy sensing models)</b>   |  | Minimum of 94 angular degrees up to a distance of 15 ft (4.6 m); based on a clear line of sight |
| <b>Ambient conditions</b>   | <b>Operating</b>   | 32°F to 122°F (0°C to 50°C); 95% RH maximum, noncondensing                                      |
|   | <b>Storage</b>   | -22°F to 122°F (-30°C to 50°C); 95% RH maximum, noncondensing                                   |

## **TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostat Controllers Catalog Page (Continued)**

### **TEC3000 Color Series Thermostat Controllers (Continued)**

|   |   |  |
|---|---|--|
|  | <b>BACnet International</b>               | BACnet Testing Laboratories™ (BTL) 135-2001 Listed BACnet Advanced Application Controller (B-AAC)  |
|   | <b>United States</b>                      | UL Listed, File E27734, CCN XAPX, Under UL60730<br><b>Networked models:</b> FCC Compliant to CFR 47, Part 15, Subpart B, Class B<br><b>Wireless models:</b> Transmission complies with FCC Part 15.247 regulations for low power unlicensed transmitters; transmitter identification FCC: OEJ-WRZRADIO |
|   | <b>Canada</b>                             | UL Listed, File E27734, CCN XAPX7, Under E60730<br><b>Networked models:</b> Industry Canada, ICES-003<br><b>Wireless models:</b> Industry Canada (IC) RSS-210; Transmitter identification ZFR1810-1: IC: 279A-WRZRADIO   |
|   | <b>Europe (for networked models only)</b> | CE Mark – Johnson Controls declares that this product is in compliance with the essential requirements and other relevant provisions of the EMC Directive and the RoHS Directive.  |
|   | <b>Australia and New Zealand</b>          | RCM Mark, Australia/NZ Emissions Compliant   |
|   | <b>Models without occupancy sensor</b>    | 0.75 lb (0.34 kg)  |
|   | <b>Models with occupancy sensor</b>       | 0.77 lb (0.35 kg)  |
| <b>Shipping weight</b>  |   |  |