

1G65-641

Line Voltage Baseboard Thermostats - Bimetal

Line voltage mechanical thermostats baseboard and resistance heat.

Features

- Rugged bimetal switch action
- · 1G66 types are a double-pole disconnect model with "OFF" position which mechanically breaks both sides of line
- Thermostat mounts on 2" X 4" electrical box
- · Classic white
- · Mercury free design

Specifications

Differential	3.0°F (1.5°C)
Set-point range	40 to 80°F (4 to 26°C)
Dimensions	4.81"H X 3.31"W X 1.44"D
Agency	UL, CSA

Parts and accessories

Description	Model number	Item number
Thermostat guard - clear plastic	F29-0198	F29-0198

See Thermostat Guards for additional options.

Line Voltage Baseboard Thermostats - Bimetal

Heat / cool	Switch action	120 Vac resistive (non-inductive)	240 Vac resistive (non-inductive)	277 Vac resistive (non-inductive)	Typical application	Model number	Item number	
Heat	Open on rise	22.0A (2500W)	22.0A (5000W)	18.0A (5000W)	Baseboard Electric Heat, Cable Heat, Glass Panels	1G65-633	1G65-633	*
Heat	Open on rise	22.0A (2500W)	22.0A (5000W)	18.0A (5000W)	Baseboard Electric Heat, Cable Heat, Glass Panels	1G65-641	01G65 641	
Heat	Open on rise	_	22.0A (5000W)	18.0A (5000W)	Baseboard Electric Heat, Cable Heat, Glass Panels	1G66-633	1G66-633	
Heat	Open on rise	-	22.0A (5000W)	18.0A (5000W)	Baseboard Electric Heat, Cable Heat, Glass Panels	1G66-641	01G66 641	*

[♣] Indicates Canadian Model Number: Call 1-800-305-6953 to order.